

VINIKA® T616

Rigid Polyvinyl Chloride

Mitsubishi Chemical Performance Polymers, Inc.

Message:

VINIKA® T616 is a Rigid Polyvinyl Chloride material. It is available in Asia Pacific for extrusion. Primary attribute of VINIKA® T616: Heat Resistant.

General Information			
Features	Medium Heat Resistance		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.46	g/cm ³	JIS K7112
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	50.0	MPa	JIS K7161
Tensile Strain (Break)	90	%	JIS K7161
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	20	kJ/m ²	JIS K7111
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	110	°C	JIS K7206 ¹
NOTE			
1.	B (50N)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT