

WPP TPO TPO-2563 P Black

Compounded Polypropylene
Washington Penn Plastic Co. Inc.

Message:

WPP TPO TPO-2563 P Black is a composite polypropylene product containing 26% mineral fillers. It is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Typical application areas are: automotive industry.
Features include:
Hard
Good toughness
Impact resistance
soft
UV stability

General Information			
Filler / Reinforcement	Mineral filler, 26% filler by weight		
Additive	UV stabilizer		
Features	Impact resistance, good		
	Medium liquidity		
	Good toughness		
	ductility		
	Medium hardness		
Uses	Application in Automobile Field		
	Automotive exterior parts		
Appearance	Black		
	Available colors		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Density	1.10	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	12	g/10 min	ISO 1133
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 15 sec)	60		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	14.0	MPa	ISO 527-2/50
Tensile Strain (Break)	200	%	ISO 527-2/50
Flexural Modulus ¹	1200	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ISO 180
-40°C	3.5	kJ/m ²	ISO 180
23°C	38	kJ/m ²	ISO 180

Instrumented Dart Impact ²			ASTM D3763
-30°C	22.0	J	ASTM D3763
23°C	18.0	J	ASTM D3763
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature			
0.45 MPa, not annealed	90.0	°C	ISO 75-2/B
1.8 MPa, not annealed	68.0	°C	ISO 75-2/A
Linear thermal expansion coefficient			ASTM E831
Flow	4.0E-5	cm/cm/°C	ASTM E831
Lateral	1.5E-4	cm/cm/°C	ASTM E831
Additional Information			
Tensile Strain at Break, ISO 527, 50mm/min: >200%			
NOTE			
1.	2.0 mm/min		
2.	2.20 m/sec		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

