CONAP® EN-5852

Polyurethane

Cytec Industries Inc.

Message:

CONAP EN-5852 is a filled, flame-retardant, two-component polyurethane system formulated for potting and encapsulating electrical and electronic components, modules, circuit boards, assemblies, and related devices.

General Information				
Features	Filled			
	Flame Retardant			
	Good Electrical Properties			
	Low Temperature Flexibility			
Uses	Electrical Parts			
	Electrical/Electronic Applications			
	Printed Circuit Boards			
RoHS Compliance	RoHS Compliant			
Appearance	Black			
	Brown			
Processing Method	Encapsulating			
	Potting			
Physical	Nominal Value	Unit		
Specific Gravity				
1	1.21	g/cm³		
²	1.45	g/cm³		
Hardness	Nominal Value	Unit		
Durometer Hardness (Shore A)	85			
Elastomers	Nominal Value	Unit		
Tensile Strength	5.93	MPa		
Tensile Elongation (Break)	180	%		
Tear Strength	28.0	kN/m		
Thermal	Nominal Value	Unit		
Glass Transition Temperature	-44.0	°C		
Thermal Conductivity	0.60	W/m/K		
Electrical	Nominal Value	Unit	Test Method	
Surface Resistivity	4.2E+15	ohms		
Volume Resistivity (25°C)	1.1E+15	ohms•cm		

Dielectric Strength (1.59 mm)	18	kV/mm	
Dielectric Constant (25°C, 1 kHz)	4.34		
Dissipation Factor (25°C, 1 kHz)	0.087		
Flammability	Nominal Value	Unit	Test Method
Flame Rating (2.80 mm)	V-0		UL 94
Thermoset	Nominal Value	Unit	
Thermoset Components			
Hardener	Mix Ratio by Weight: 100		
Resin	Mix Ratio by Weight: 20		
Thermoset Mix Viscosity (25°C)	8500	сР	
NOTE			
1.	Resin		
2.	Hardener		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

