

Europrene Latice® 084

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

Message:

Europrene Latice 084 is an aqueous anionic dispersion of a styrene-butadiene copolymer with low solid content obtained by emulsion polymerisation using fatty acid soap as emulsifier. It does not contain any antioxidant.

Key Features

Europrene Latice 084 can be blended with VPL and natural latex

Main Applications

Europrene Latice 084 is mainly used for fabric impregnation and tyre cord dipping

General Information			
Features	Copolymer		
Uses	Blending		
	Impregnation Applications		
Appearance	White		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Bound Styrene	24.0	%	ASTM D5775
pH	11.3		ASTM D1417
Solids Content	41.0	wt%	ASTM D1417
Brookfield Viscosity ¹ (25°C)	< 200	mPa · s	ASTM D1417
NOTE			
1.	20 rpm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT