SABIC® PPcompound 8750U

Polypropylene

Saudi Basic Industries Corporation (SABIC)

Message:

SABIC® Prompound 8750U is a development grade, elastomer-modified mineral filled Polypropylene for unpainted automotive exterior applications. The grade is UV stabilized and has been designed to combine a good performance profile with good processing.

SABIC® Prompound 8750U is a designated automotive grade.

General Information					
Filler / Reinforcement	Mineral				
Additive	Impact Modifier				
	UV Stabilizer				
Features	Good Processability				
	Good UV Resistance				
	Impact Modified				
Uses	Automotive Applications				
	Automotive Exterior Parts				
Forms	Pellets				
Processing Method	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Density	1.01	g/cm³	ISO 1183		
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	18	g/10 min	ISO 1133		
Molding Shrinkage (24 hr)	0.80	%	Internal Method		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Stress			ISO 527-2/1A/50		
Yield, Injection Molded	20.0	MPa			
Break, Injection Molded	13.5	MPa			
Tensile Strain (Break, Injection Molded)	80	%	ISO 527-2/1A/50		
Flexural Modulus ¹ (Injection Molded)	1750	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact Strength			ISO 180/4A		
-20°C, Injection Molded	7.0	kJ/m²			
0°C, Injection Molded	20	kJ/m²			
23°C, Injection Molded	50	kJ/m²			
Thermal	Nominal Value	Unit	Test Method		
Heat Deflection Temperature (0.45 MPa, Unannealed)	105	°C	ISO 75-2/B		

CLTE - Flow			ASTM D696
-30 to 30°C	6.0E-5	cm/cm/°C	
23 to 80°C	8.0E-5	cm/cm/°C	
NOTE			

. Method I (3 point load)

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

