

# Sylvin 2965-50 Natural

Polyvinyl Chloride  
Sylvin Technologies Incorporated

Message:

Sylvin 2965-50 Natural Is A Vinyl Compound Formulated With FDA Sanctioned Ingredients For Profile Extrusion Applications.

General Information	
Uses	Profile
Agency Ratings	FDA not rated
Appearance	Natural color
Processing Method	Extrusion Profile extrusion molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.26	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	50		ASTM D2240
Shaw A, 10 seconds	50		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	8.96	MPa	ASTM D638
Tensile Elongation (Break)	450	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	26.3	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	149 - 160	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT