

# Cosmic Epoxy CP7311

Epoxy; Epoxide

Cosmic Plastics, Inc.

## Message:

### DESCRIPTION

Cosmic CP7311 is a long glass reinforced epoxy molding compound which is supplied in a flake form.

### FEATURES

Can be compression or transfer molded, and has high physical strength. This material has a shelf life of 18 months when stored at 20°C or less.

### APPLICATIONS

Makes an ideal replacement for many aircraft and heavy metal parts.

General Information	
Filler / Reinforcement	Long Glass Fiber
Features	High Strength
Uses	Aircraft Applications
	Metal Replacement
Forms	Flakes
Processing Method	Compression Molding
	Resin Transfer Molding

Physical	Nominal Value	Unit
Specific Gravity	2.19	g/cm <sup>3</sup>
Bulk Factor	10	
Mechanical	Nominal Value	Unit
Tensile Strength	103 to 186	MPa
Flexural Strength	241 to 310	MPa
Compressive Strength	179 to 262	MPa
Impact	Nominal Value	Unit
Notched Izod Impact	1300 to 1800	J/m
Injection	Nominal Value	Unit
Processing (Melt) Temp	130 to 180	°C
Injection Pressure	3.45 to 55.2	MPa

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

**Susheng Import & Export Trading Co., Ltd.**

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

