

# Sylvin 8957-80 BLACK

Polyvinyl Chloride  
Sylvin Technologies Incorporated

Message:  
Sylvin 8957-80 Black Is A Vinyl Compound Formulated For Extrusion Or Molding Applications. This Compound Meets The Requirements Of GMP PVC.007 And GMP PVC .009.

General Information	
Uses	Automotive Applications
Appearance	Black
Forms	Pellets
Processing Method	Extrusion Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.31	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	80		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	15.2	MPa	ASTM D638
Tensile Elongation (Break)	370	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	66.5	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	166 to 177	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT