

# MAZMID C 380/330S

Polyamide 6

Mazzaferro Indústria e Comércio de Polímeros e Fibras Ltda.

Message:

MAZMID C 380/330S is a Polyamide 6 (Nylon 6) product. It can be processed by extrusion and is available in Latin America. Typical application: Film.  
Characteristics include:  
Clarity  
Copolymer  
Good Tear Strength  
High Gloss  
Lubricated

General Information			
Additive	Lubricant		
Features	Copolymer		
	Gas Barrier		
	Good Tear Strength		
	High Clarity		
	High Gloss		
	Lubricated		
Uses	Film		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.11 to 1.13	g/cm³	ASTM D792
Apparent Density	0.65	g/cm³	ASTM D1895
Melt Mass-Flow Rate (MFR) (235°C/2.16 kg)	6.0 to 8.0	g/10 min	ASTM D1238
Viscosity Number	178 to 190	cm³/g	ISO 307
Ash Content	None		
Moisture Content	< 800	ppm	
Relative Viscosity - H2SO4	3.15 to 3.40		
Monomers	< 0.70	%	
Thermal	Nominal Value	Unit	
Melting Temperature	195 to 200	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

