

Xuchuan XCW-85H-12

Polyurethane

Xuchuan Chemical (Suzhou) Co., Ltd

Message:

Xuchuan XCW-85H-12 is a Polyurethane product. It is available in Asia Pacific. Typical application: Consumer Goods.

General Information		
Features	Hydrolysis Resistant	
	Medium Hardness	
Uses	Footwear	
	Synthetic Leather	
Physical	Nominal Value	Unit
Solids Content	29 to 31	%
Viscosity (25°C)	120 to 180	Pa·s
Solvents	DMF	
Elastomers	Nominal Value	Unit
Tensile Stress (100% Strain)	8.34	MPa
Tensile Strength (Break)	44.1	MPa
Tensile Elongation (Break)	400	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT