ARK 2150-60A

Thermoplastic Polyurethane Elastomer (Polyester)

Arkadia Plastics, Inc.

Message:

thermoplastic polyurethane alloys, is a class of soft TPU materials that have been formulated by blending TPUs with soft rubbers and other proprietary additives to improve compatibility and exhibits outstanding properties

General Information				
Additive	UV Stabilizer			
Features	Excellent Elastic Recovery			
	Good Abrasion Resistance			
	Good Chemical Resistance			
	Good Flexibility			
	Good Processability			
	Good UV Resistance			
	High Clarity			
	High Elasticity			
	Hydrolytically Stable			
	Oil Resistant			
	Soft			
Uses	Business Equipment			
	Computer Components			
	Film			
	Medical/Healthcare Applications			
	Overmolding			
	Power/Other Tools			
	Sheet			
	Sporting Goods			
	Tubing			
Forms	Pellets			
Processing Method	Extrusion			
	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.10	g/cm³	ASTM D792	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	60		ASTM D2240	
Elastomers	Nominal Value	Unit	Test Method	

Tensile Stress			ASTM D412
100% Strain	1.62	MPa	
300% Strain	3.17	MPa	
Tensile Strength (Yield)	22.8	MPa	ASTM D412
Tensile Elongation (Break)	540	%	ASTM D412
Tear Strength	43.8	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	-50.0	°C	ASTM E1356
Injection	Nominal Value	Unit	
Drying Temperature	71.1 to 76.7	°C	
Processing (Melt) Temp	204 to 227	°C	
Extrusion	Nominal Value	Unit	
Drying Temperature	71.1 to 76.7	°C	
Melt Temperature	191 to 227	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

