

S&E; Footwear GFE-1815

Polyvinyl Chloride + NBR
S&E; Specialty Polymers, LLC

Message:
Expandable PVC/Nitrile, oil resistant

General Information			
Features	Expandable		
	Oil Resistant		
Uses	Footwear		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.20	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	68		
Shore A, 3 sec	60		
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	11.7	MPa	ASTM D412
Tensile Elongation (Break)	380	%	ASTM D412
Additional Information	Nominal Value	Unit	
Stock Temperature	166 to 171	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT