

OLEFISTA™ QX0238C

Specialty Elastomer

Mitsubishi Chemical Performance Polymers, Inc.

Message:

OLEFISTA™ QX0238C is a Specialty Elastomer material. It is available in Asia Pacific.

Important attributes of OLEFISTA™ QX0238C are:

Flame Rated

Flame Retardant

General Information		
Features	Flame Retardant	
	Halogenated	
Physical	Nominal Value	Unit
Specific Gravity	1.29	g/cm ³
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A, 10 sec)	90	
Elastomers	Nominal Value	Unit
Tensile Stress (Break)	19.0	MPa
Tensile Elongation (Break)	850	%
Aging	Nominal Value	Unit
Change in Tensile Strength in Air (136°C, 168 hr)	75	%
Change in Tensile Strain at Break in Air (136°C, 168 hr)	80	%
Flammability	Nominal Value	Test Method
Flame Rating (1.00 mm)	V-0	UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT