PolyMax™ HD

High Density Polyethylene

Heritage Plastics, Inc.

Message:

Formulated to maximize the cost and performance balance in a wide variety of HDPE blow molding applications. Ideal for maintaining stiffness and top load strengths.

Suitable Applications:

blow molding

furniture

oil bottles

juice and dairy bottles

garbage cans

flower pots

Environmentally Beneficial

Calcium carbonate is a plentiful, natural mineral and can be used to effectively displace a significant portion of the petrochemical based component in the targeted application. The improved productivity and the lower energy consumption awarded by using our concentrates all help to minimize the carbon footprint of the end product.

Regulatory Compliance

The ingredients in our concentrates are approved for use in direct food contact packaging and are heavy metals free making them compliant with regulations such as California Proposition 65 and CONEG.

General Information				
Filler / Reinforcement	Calcium Carbonate,76%	Calcium Carbonate,76% Filler by Weight		
Features	Food Contact Acceptable			
	Good Stiffness			
	Good Strength			
Uses	Blow Molding Applications			
	Bottles			
	Fruit Juice Bottles			
	Furniture			
Processing Method	Blow Molding	Blow Molding		
Physical	Nominal Value	Unit	Test Method	
Density	1.85	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (190°C/2.	16			
kg)	1.5	g/10 min	ASTM D1238	
Moisture Content	< 1000	ppm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

