

Silmar® SIL95BA-41

Thermoset Polyester
Interplastic Corporation

Message:

We offer hundreds of specially designed resins that integrate easily into your production requirements - delivering superior results and meeting current environmental standards.
SIL95BA-41 is perfect for large clear casting applications. This resin has low viscosity, medium gel time, low exotherm, low shrinkage and exceptional clarity.

| General Information | | |
|---|-------------------|------|
| Features | High Clarity | |
| | Low Exotherm | |
| | Low Shrinkage | |
| | Low Viscosity | |
| Uses | Decorative Parts | |
| | Transparent Parts | |
| Additional Information | Nominal Value | Unit |
| Gel to Peak | 40.0 to 55.0 | |
| Uncured Properties | Nominal Value | Unit |
| Viscosity ¹ (Brookfield HBT) | 0.40 to 0.50 | Pa·s |
| Gel Time | 20 to 30 | min |
| NOTE | | |

1. RV #2 at 20 RPM

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT