

# Sanren EVA 14/15

Ethylene Vinyl Acetate Copolymer  
SINOPEC Shanghai Petrochemical Co. Ltd.

Message:

The product is a colourless oblate pellet with excellent chemical stability, flexibility and adhesion properties. It possesses certain impact resistance, good stress-fracture resistance and fine light transmittance.  
Scope of Application: Small size injection mouldings

General Information			
Features	Copolymer		
	Good Adhesion		
	Good Flexibility		
	Good Impact Resistance		
	High ESCR (Stress Crack Resist.)		
	High Light Transmission		
Appearance	Colorless		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)	12 to 18	g/10 min	Internal Method
Vinyl Acetate Content	12.0 to 16.0	wt%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	> 8.30	MPa	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT