

UBE Nylon 5034 TX18

Polyamide 66/6 Copolymer

UBE Engineering Plastics, S.A.

Message:

UBE NYLON 5034 TX18 is a high viscosity Polyamide 6/6.6 copolymer for monofilament application, both for small and large diameter size. The material allows high drawing ratios resulting in superior line strength.

General Information			
Features	Workability, good		
	Definition, high		
	Viscosity, High		
Uses	monofilament		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Density	1.14	g/cm ³	ISO 1183
Thermal	Nominal Value	Unit	Test Method
Melting Temperature (DSC)	191	°C	ISO 3146
Additional Information			

The value listed as Melting Temperature, ISO 3146, was tested in accordance with ISO 11357. Relative Viscosity, JIS K6810, 96% H₂SO₄, conc. 1.0 g/100 ml: 4.05 Extractable Content, JIS K6810: <1.0 wt% Molecular Ratio, PA6/PA6.6: 85/15

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

