ALFATER XL® D40I 3EF0001

Thermoplastic Vulcanizate

ALBIS PLASTIC GmbH

Message:

ALFATER XL® D40I 3EF0001 is a Thermoplastic Vulcanizate (TPV) product. It is available in Asia Pacific, Europe, or North America. Applications of ALFATER XL® D40I 3EF0001 include automotive, construction applications, engineering/industrial parts and sealing applications.

Characteristics include:

REACH Compliant

RoHS Compliant

Good Aesthetics

Good Weather Resistance

High Flow

| General Information | | | | |
|---|---------------------------|-------|-------------|--|
| Additive | UV Stabilizer | | | |
| Features | Alkali Resistant | | | |
| | Good Surface Finish | | | |
| | Good Weather Resistance | | | |
| | High Flow | | | |
| | Ozone Resistant | | | |
| | | | | |
| Uses | Automotive Applications | | | |
| | Construction Applications | | | |
| | Seals | | | |
| | Thin-walled Parts | | | |
| | | | | |
| Agency Ratings | EC 1907/2006 (REACH) | | | |
| RoHS Compliance | RoHS Compliant | | | |
| Physical | Nominal Value | Unit | Test Method | |
| Density | 0.950 | g/cm³ | ISO 1183 | |
| Hardness | Nominal Value | Unit | Test Method | |
| Shore Hardness (Shore D) | 40 | | ISO 868 | |
| Mechanical | Nominal Value | Unit | Test Method | |
| Tensile Stress (100% Strain) | 9.70 | MPa | ISO 527-2 | |
| Elastomers | Nominal Value | Unit | Test Method | |
| Tensile Stress (Yield) | 12.4 | MPa | ISO 37 | |
| Tensile Elongation (Break) | 500 | % | ISO 37 | |
| Tear Strength | 62 | kN/m | ISO 34-1 | |
| Compression Set ¹ (100°C, 22 hr) | 80 | % | ISO 815 | |
| Thermal | Nominal Value | Unit | | |
| Service Temperature | -40 to 125 | °C | | |
| Injection | Nominal Value | Unit | | |

| Drying Temperature | 70.0 to 80.0 | °C | |
|------------------------|---------------|----|--|
| Drying Time | 2.0 to 4.0 | hr | |
| Processing (Melt) Temp | 195 to 215 | °C | |
| Mold Temperature | 10.0 to 70.0 | °C | |
| Injection Rate | Moderate-Fast | | |
| NOTE | | | |
| 1. | 25% | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

