

SABIC® LDPE Powder 1965P5

Low Density Polyethylene
Saudi Basic Industries Corporation (SABIC)

Message:

SABIC® LDPE Powder 1965P5 is an additive free standard CTR® tubular grade with a typically high melt flow rate and is known for its typically high filler/pigments acceptance properties. This grade is supplied in powder form.

Application

SABIC® LDPE Powder 1965P5 is a medium sized powder grade with a typically low viscosity for textile coating, carpet backing and compounding applications. It is further typically suited for masterbatches with a typically very high loading of carbon black, titanium dioxide or pigment. This product is not intended for and must not be used in any pharmaceutical/medical applications.

General Information			
Features	Additive Free		
	High Flow		
	Low Density		
	Low Viscosity		
Uses	Carpet Backing		
	Coating Applications		
	Compounding		
	Masterbatch		
	Textile Applications		
Forms	Powder		
Processing Method	Compounding		
Physical	Nominal Value	Unit	Test Method
Density	0.919	g/cm³	ISO 1183
Apparent Density	0.34	g/cm³	ISO 60
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	65	g/10 min	ISO 1133
Particle Size - Powder	< 600	µm	ASTM E1181
Enthalpy Change	95.0	J/g	DIN 53765
Dry Flow	23.0	sec	ISO 6186
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	75.0	°C	ISO 306/A
Melting Temperature (DSC)	104	°C	DIN 53765

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

