

Cheng Yu PP222

Polypropylene

Cheng Yu Plastic Company Limited

Message:

Cheng Yu PP222 is a Polypropylene product. It is available in Asia Pacific.

Characteristics include:

- Flame Rated
- Flame Retardant
- Impact Resistant

General Information			
UL YellowCard	E159271-224216		
Additive	Flame Retardant		
Features	Flame Retardant		
	High Impact Resistance		

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.908	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR)	10 to 15	g/10 min	ASTM D1238
Molding Shrinkage			ASTM D955
Flow	1.1 to 1.5	%	
Across Flow	1.1 to 1.5	%	
Water Absorption (Saturation)	0.010	%	ASTM D570

Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (M-Scale)	100		ASTM D785

Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	30.0	MPa	ASTM D638
Flexural Strength	63.0	MPa	ASTM D790

Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (23°C)	47	J/m	ASTM D256

Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	125	°C	ASTM D648

Electrical	Nominal Value	Unit	Test Method
Surface Resistivity	1.0E+15	ohms	ASTM D257

Flammability	Nominal Value	Unit	Test Method
Flame Rating (1.50 mm)	V-2		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

