

TABOREX TA 2144 HD

Thermoplastic

SILON s.ro

Message:

Masterbatch for the use with SILON Silane crosslinkable PE-Xb Compounds TABOREX.

TABOREX TA 2144 HD contains the cross-linking catalyst and a stabilizer package. Together with Silon's Silane grafted TABOREX Compounds this masterbatch completes a Sioplas System (PE-Xb) and provides processing and long term stability to the final product.

Application: TABOREX TA 2144 HD is a catalyst masterbatch according to the Sioplas system for the production of pipes for sanitary and heating applications.

General Information			
Features	Crosslinkable		
	Food Contact Acceptable		
Uses	Masterbatch		
Agency Ratings	BfR Food Contact, Unspecified Rating		
	FDA Unspecified Rating		
Appearance	Opaque		
	White		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.960	g/cm ³	ASTM D792
Apparent Density	0.53	g/cm ³	ASTM D1895
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	8.0	g/10 min	ASTM D1238
Moisture	< 0.010	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT