ORIENTENE FB 12

Polypropylene Homopolymer

Oriental Petrochemical Company

Message:

 $ORIENTENE\ FB\ 12\ is\ a\ Polypropylene\ Homopolymer\ (PP\ Homopolymer)\ material.\ It\ is\ available\ in\ Africa\ \&\ Middle\ East.$

Food Contact Acceptable

Important attributes of ORIENTENE FB 12 are:

Food Contact Acceptable

Good Processability

Typical applications include:

Fabrics/Fibers

Features

Food Contact Applications

General Information

Yarn

	Gas-fading Resistant		
	Good Color Stability		
	Good Processing Stability		
Uses	BCF Yarn		
uses			
	Fibers		
	Staple Fibers		
Agency Ratings	EU 2002/72/EC		
	FDA 21 CFR 177.1520(c) 1.1		
Physical	Nominal Value	Unit	Test Method
Density	0.905	g/cm³	ISO 1183, ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	12	g/10 min	ASTM D1238, ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	34.5	MPa	ASTM D638
Tensile Elongation ² (Yield)	7.0	%	ASTM D638
Flexural Modulus - 1% Secant ³	1380	МРа	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	23	J/m	ASTM D256A
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	104	°C	ASTM D648
NOTE			
1.	50 mm/min		
2.	50 mm/min		
3.	1.3 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

