# **ADDINYL A2 G30**

### Polyamide 66

#### **ADDIPLAST**

#### Message:

ADDINYL A2 G30 is a Polyamide 66 (Nylon 66) material filled with 30% glass bead. It is available in Africa & Middle East, Asia Pacific, Europe, or Latin America.

Important attributes of ADDINYL A2 G30 are:

Good Dimensional Stability

Rigid

Typical application of ADDINYL A2 G30: Automotive

General Information						
Filler / Reinforcement		Glass Bead,30% Filler by Weight				
Features		Good Dimensional Stability				
		High Rigidity				
Uses		Automotive Applications				
		Automotive Under the Hood				
_		- u .				
Forms		Pellets				
Physical	Dry	Conditioned	Unit	Test Method		
Density	1.35		g/cm³	ISO 1183/A		
Hardness	Dry	Conditioned	Unit	Test Method		
Shore Hardness (Shore D)	87	82		ISO 868		
Mechanical	Dry	Conditioned	Unit	Test Method		
Tensile Stress (Break)	80.0	60.0	MPa	ISO 527-2		
Tensile Strain (Break)	7.0	11	%	ISO 527-2		
Flexural Modulus	3800	1800	MPa	ISO 178		
Impact	Dry	Conditioned	Unit	Test Method		
Charpy Notched Impact Strength	3.0	5.0	kJ/m²	ISO 179/1eA		
Charpy Unnotched Impact Strength	40	60	kJ/m²	ISO 179/1eU		
Notched Izod Impact Strength	3.5	7.0	kJ/m²	ISO 180/1A		
Thermal	Dry	Conditioned	Unit	Test Method		
Heat Deflection Temperature (1.8 MPa, Unannealed)	95.0		°C	ISO 75-2/Af		
Melting Temperature (DSC)	260		°C	ISO 3146		
CLTE - Flow	6.0E-5		cm/cm/°C	ASTM E831		
Electrical	Dry	Conditioned	Unit	Test Method		
Volume Resistivity	1.0E+15	1.0E+13	ohms·cm	IEC 60093		

Electric Strength	30	25	kV/mm	IEC 60243-1
Comparative Tracking				
Index (Solution A)	600		V	IEC 60112

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

