

Hanwha Total PP TH54I

Polypropylene

HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:

TH54I is a high crystalline polypropylene compound featuring superior flexural modulus, surface hardness and tensile strength. TH54I is very effective in reducing material weight. Primary uses include those for shrouds, temperature valves and air cleaner housings. Improvement in the recycling of this product has been accomplished by substituting Nylon+G/F or PP+G/F due to its superior properties. This product is ideally suited for use in engines and air-conditioning system parts due to exceptional heat resistance.

General Information			
Additive	Antistatic property		
Features	Rigidity, high		
	High tensile strength		
	Crystallization		
	Antistatic property		
	Recyclable materials		
	Workability, good		
	Scratch resistance		
	Heat resistance, high		
	High hardness		
Uses	Parts under the hood of a car		
	Shell		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	1.23	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	6.0	g/10 min	ASTM D1238
Molding Shrinkage - Flow	0.60 - 1.0	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	102		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	35.8	MPa	ASTM D638
Fracture	29.4	MPa	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	29	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	159	°C	ASTM D648

Additional Information

Elongation @ Break, ASTM D790: 54000 kg-cm/cm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

