Moplen HP420J

Polypropylene Homopolymer

PolyMirae

Message:

Moplen HP420J is a Polypropylene Homopolymer (PP Homopolymer) material. It is available in Asia Pacific.

Important attributes of Moplen HP420J are:

Food Contact Acceptable

Good Aesthetics

Good Processability

Homopolymer

Typical applications include:

Adhesives/Tapes

Coating Applications

Film

Food Contact Applications

General Information				
Features	Food Contact Acceptable			
	General Purpose			
	Good Processability			
	Good Stretchability			
	Homopolymer			
	Opticals			
Uses	Adhesives			
	Bi-axially Oriented Film			
	General Purpose			
	Laminates			
	Tape			
Agency Ratings	FDA 21 CFR 177.1520			
Forms	Pellets			
Physical	Nominal Value	Unit	Test Method	
Density	0.900	g/cm³	ASTM D1505	
Melt Mass-Flow Rate (MFR) (230°C/2.16				
kg)	3.0	g/10 min	ASTM D1238	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	95		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield, Injection Molded)	32.4	MPa	ASTM D638	
Tensile Elongation (Yield, Injection Molded)	12	%	ASTM D638	
Flexural Modulus (Injection Molded)	Naminal Value	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	

Notched Izod Impact (23°C, Injection					
Molded)	39	J/m	ASTM D256		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load (0.45					
MPa, Unannealed, Injection Molded)	102	°C	ASTM D648		
Vicat Softening Temperature	152	°C	ASTM D1525		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

