Lucky Enpla LKG

Acrylonitrile Butadiene Styrene Lucky Enpla Co LTD

Message:

Lucky Enpla LKG is an acrylonitrile butadiene styrene (ABS) product. It can be processed by injection molding and is available in North America, Europe or the Asia-Pacific region. Typical application areas are: electrical/electronic applications.

| General Information | | | |
|--|------------------------------------|-----------------------------------|-----------------------|
| Features | General | | |
| Uses | Electrical/Electronic Applicat | ions | |
| Processing Method | Injection molding | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.14 | g/cm³ | ASTM D792 |
| Melt Mass-Flow Rate (MFR) (220°C/10.0 | | | |
| kg) | 35 | g/10 min | ASTM D1238 |
| Molding Shrinkage - Flow | 0.40 - 0.70 | % | ASTM D955 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength ¹ | 47.1 | MPa | ASTM D638 |
| Flexural Modulus ² | 2400 | МРа | ASTM D790 |
| Flexural Strength ³ | 75.5 | МРа | ASTM D790 |
| Impact | Nominal Value | Unit | Test Method |
| Unnotched Izod Impact | | | ASTM D256 |
| 3.18 mm | 250 | J/m | ASTM D256 |
| 6.35 mm | 250 | J/m | ASTM D256 |
| Thermal | Nominal Value | Unit | Test Method |
| Deflection Temperature Under Load (1.8 MPa, Unannealed) | 91.0 | °C | ASTM D648 |
| Injection | Nominal Value | Unit | |
| Drying Temperature | 70.0 - 90.0 | °C | |
| Drying Time | 2.0 - 3.0 | hr | |
| Rear Temperature | 210 - 230 | °C | |
| Middle Temperature | 220 - 240 | °C | |
| Front Temperature | 220 - 240 | °C | |
| Nozzle Temperature | 220 - 240 | °C | |
| Mold Temperature | 60.0 - 80.0 | °C | |
| Back Pressure | 1.96 - 3.92 | MPa | |
| Screw Speed | 60 - 80 | rpm | |
| Injection instructions | | | |
| Resin Temperature: 210-230°CInjection Pre | ssure (1st Pressure): 700-1200 kg/ | 'cm²Injection Pressure (2nd Press | sure): 400-800 kg/cm² |
| NOTE | | | |
| 1. | 50 mm/min | | |

| 2. | 10 mm/min |
|----|-----------|
| 3 | 10 mm/min |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



Page 2