Shandong Aobang TPU-Polyester 85-A

Thermoplastic Polyurethane Elastomer (Polyester)

Shandong Aobang Chemical Technology Co., Ltd.

Message:

Shandong Aobang TPU-Polyester 85-A is a Thermoplastic Polyurethane Elastomer (Polyester) (TPU-Polyester) product. It is available in Asia Pacific. Applications of Shandong Aobang TPU-Polyester 85-A include additive/masterbatch, consumer goods, industrial applications and sealing applications.

General Information			
Uses	Blending		
	Footwear		
	Industrial Applications		
	Plastics Modification		
	Seals		
	Wheels		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore A)	83 to 87		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Abrasion Resistance	30.0	mm³	DIN 53516
Service Temperature	185 to 205	°C	
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress			ASTM D412
100% Strain	> 6.00	MPa	
300% Strain	> 14.0	MPa	
Tensile Strength (Break)	> 35.0	MPa	ASTM D412
Tensile Elongation (Break)	> 500	%	ASTM D412
Tear Strength	> 100	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	-38.0	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

