

Manner Flexible PVC X4787

Flexible Polyvinyl Chloride

Manner Plastics, L.P.

Message:

FDA (food grade) transparent compound suitable for tubing, profile extrusion and certain injection molding applications. All ingredients in this compound are approved for food contact by the FDA. This product complies with the European Union Restriction on Hazardous Substances (RoHS) directive.

General Information	
Features	Food Contact Acceptable
Uses	Profiles
	Tubing
Agency Ratings	FDA Food Contact, Unspecified Rating
RoHS Compliance	RoHS Compliant
Appearance	Clear/Transparent
Processing Method	Extrusion
	Injection Molding
	Profile Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21 to 1.25	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	87		
Shore A, 15 sec	81		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
0.762 mm	21.9	MPa	
100% Strain,0.762 mm	10.2	MPa	
Tensile Elongation (Break, 0.762 mm)	390	%	ASTM D638
Aging	Nominal Value	Unit	Test Method
Change in Tensile Strength in Air (110°C, 168 hr)	6.0	%	ASTM D573
Change in Ultimate Elongation in Air (110°C, 168 hr)	3.0	%	ASTM D573
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-25.0	°C	ASTM D746

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

