

# PIVINEL™ KAZ-12

Polyvinyl Chloride

HELLENIC CABLES S.A.

## Message:

Description: PVC based compounds for first sheaths (filler) in flame retardant power cables for low temperatures

Specifications: PVC bending low temperature.

Packaging: In PE bags of 25 kg or in big bags of approximately 1000 kg

Types of cables where it can be used: Armored flame retardant power cables for polar conditions

General Information		
Features	Flame Retardant	
	Low Temperature Resistant	
Uses	Wire & Cable Applications	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Specific Gravity	1.61	g/cm <sup>3</sup>
Extrusion	Nominal Value	Unit
Cylinder Zone 1 Temp.	145	°C
Cylinder Zone 2 Temp.	150	°C
Cylinder Zone 3 Temp.	150	°C
Cylinder Zone 4 Temp.	160	°C
Cylinder Zone 5 Temp.	160	°C
Cylinder Zone 6 Temp.	165	°C
Head Temperature	165	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

