

SABIC® LDPE Powder 1922P9

Low Density Polyethylene

Saudi Basic Industries Corporation (SABIC)

Message:

SABIC® LDPE Powder 1922P9 is an additive free CTR® tubular grade with a typically high purity and as such a fine material for masterbatches in film applications.

Application

SABIC® LDPE Powder 1922P9 is a normal sized powder grade. Since the grade is supplied in powder form it is typically suited for pre mixing. The flow and dispersion of pigments and additives that tend towards blocking are typically improved by adding this grade.

This product is not intended for and must not be used in any pharmaceutical/medical applications.

General Information			
Features	Additive Free		
	High Purity		
	Low Density		
Uses	Compounding		
	Film		
	Masterbatch		
Forms	Powder		
Processing Method	Compounding		
Physical	Nominal Value	Unit	Test Method
Density	0.919	g/cm ³	ISO 1183
Apparent Density	0.33	g/cm ³	ISO 60
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	22	g/10 min	ISO 1133
Particle Size - Powder	< 900	µm	ASTM E1181
Enthalpy Change	104	J/g	DIN 53765
Dry Flow	25.0	sec	ISO 6186
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	83.0	°C	ISO 306/A
Melting Temperature (DSC)	107	°C	DIN 53765

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

