

Sylvin 8409-70UV Natural

Polyvinyl Chloride + PUR
Sylvin Technologies Incorporated

Message:

Sylvin 8409-70UV Natural Is A Flexible Thermoplastic Alloy Compound Of Vinyl And Polyurethane Formulated For Extrusion Or Molding Applications That Require Increased Abrasion And Chemical Resistance. This Compound Contains A Ultra Violet Stabilizer.

General Information	
Additive	UV Stabilizer
Features	Good Abrasion Resistance
	Good Chemical Resistance
	Good UV Resistance
Appearance	Natural Color
Processing Method	Extrusion
	Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.30	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	70		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	12.4	MPa	ASTM D638
Tensile Elongation (Break)	430	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	48.2	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	160 to 171	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT