

# Bapolene® 5065NB

Polypropylene Impact Copolymer

Bamberger Polymers, Inc.

## Message:

Key Features:

Superior low temperature resistance

Material Notes:

Description: Impact copolymer for injection molding applications. It is nucleated and exhibits superior low temperature resistance.

Applications: Injection molding and compounding.

General Information	
Additive	Nucleating Agent
Features	Impact Copolymer
	Low Temperature Resistant
	Nucleated
Uses	Compounding
Forms	Pellets
Processing Method	Compounding
	Injection Molding

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	15	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus - 1% Secant	965	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	No Break		ASTM D256A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT