

# Geon™ Vinyl Flexible R267AM

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™ Vinyl Flexible R267AM is a Flexible Polyvinyl Chloride product. It can be processed by extrusion or injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Furniture. Primary characteristic: high gloss.

General Information	
Features	General Purpose
	High Gloss
Uses	Furniture
	General Purpose
Appearance	Clear/Transparent
Forms	Pellets
Processing Method	Extrusion
	Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.30	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	60		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength <sup>1</sup> (Break)	21.7	MPa	ASTM D638
Tensile Elongation <sup>2</sup> (Break)	250	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-6.11	°C	ASTM D746
Injection	Nominal Value	Unit	
Processing (Melt) Temp	191 to 202	°C	
Extrusion	Nominal Value	Unit	
Melt Temperature	179 to 185	°C	

NOTE	
1.	Type IV, 510 mm/min
2.	Type IV, 510 mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

