

Bolv ABS

Acrylonitrile Butadiene Styrene
Shandong Jining Bolv Chemicals Co.,Ltd

Message:
Bolv ABS is an Acrylonitrile Butadiene Styrene (ABS) material. It is available in Asia Pacific.

General Information			
Physical	Nominal Value	Unit	Test Method
Density	2.15	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	11	g/10 min	ASTM D1238
Water Absorption (Equilibrium)	0.20	%	ASTM D570
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	41.0	MPa	ASTM D638
Tensile Elongation (Break)	25	%	ASTM D638
Flexural Strength (Yield)	3.78	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (Area)	24.0	kJ/m ²	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	110	°C	ASTM D648
Vicat Softening Temperature	> 100	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT