

Kumho KNB 35LL

Acrylonitrile Butadiene Rubber
Korea Kumho Petrochemical Co., Ltd.

Message:
Kumho KNB 35LL is an Acrylonitrile Butadiene Rubber (NBR) material. It is available in Asia Pacific, Europe, or North America.

General Information			
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity ¹	27 to 37	MU	ASTM D1646
Ash Content	0.80	%	ASTM D5667
Volatile Matter	0.50	%	ASTM D5668
Bound AN	32 to 36	%	
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (200% Strain)	10.8 to 16.7	MPa	ASTM D412
Tensile Strength (Break)	20.6	MPa	ASTM D412
Tensile Elongation (Break)	450	%	ASTM D412
NOTE			

1. Raw, ML1+4 at 100°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

