

Inverko e-P0502KG

Polypropylene

Inverko Compounding B.V.

Message:

Inverko e-P0502KG is a Polypropylene product. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America.

General Information			
Appearance	Dark Green		
Forms	Pellets, Reprocessed		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	0.972	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	2.0 to 4.0	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (23°C)	> 590	MPa	ISO 527-2/1A/1
Tensile Stress (Yield, 23°C)	> 20.0	MPa	ISO 527-2/1A/50
Tensile Strain (Break, 23°C)	> 280	%	ISO 527-2/1A/50
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	> 7.0	kJ/m ²	ISO 180/1A
Unnotched Izod Impact Strength (23°C)	No Break		ISO 180/1U

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT