

Indothene 1005FY20

Low Density Polyethylene

Reliance Industries Limited

Message:

Indothene 1005FY20 is a Low Density Polyethylene product. It is available in Africa & Middle East, Asia Pacific, or Europe.

General Information			
Forms	Granules		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.50	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Coefficient of Friction	0.22		ASTM D1894
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD : Break	21.1	MPa	
TD : Break	19.6	MPa	
Tensile Elongation			ASTM D882
MD : Break	300	%	
TD : Break	530	%	
Dart Drop Impact	150	g	ASTM D1709

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT