

SAPYLENE MC75LTD

Linear Low Density Polyethylene

Sahel Chimie Co.

Message:

SAPYLENE MC75LTD is a Linear Low Density Polyethylene material. It is available in Africa & Middle East for injection molding.

Important attributes of SAPYLENE MC75LTD are:

High Hardness

Non-Toxic

Typical applications include:

Additive/Masterbatch

Bags/Liners

Film

Plumbing/Piping/Potable Water

Sheet

General Information			
Features	Excellent Printability		
	High Hardness		
	Non-Toxic		
Uses	Bags		
	Cable Jacketing		
	Film		
	Masterbatch		
	Piping		
	Profiles		
	Sheet		
Processing Method		Injection Molding	
Physical	Nominal Value	Unit	Test Method
Density	1.40	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	1.0 to 20	g/10 min	ASTM D1238
Humidity	< 0.20	%	Internal Method
Filler Content (650°C)	75	%	ASTM D1603
Thermal	Nominal Value	Unit	
Melting Temperature	130	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

