

SWANCOR Epoxy 905-N

Epoxy; Epoxide
SWANCOR IND. CO., LTD.

Message:

Combination of flame retardance, improved elevated heat resistance and excellent chemical resistance.
Meet ASTM E84 Class 1 while incorporated with 3-5% Antimony Trioxide

General Information			
Filler / Reinforcement	Styrene,38% Filler by Weight		
Features	Flame Retardant		
	Good Chemical Resistance		
	High Heat Resistance		
Agency Ratings	ASTM E 84		
Forms	Liquid		
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	133	°C	ASTM D648
Thermoset	Nominal Value	Unit	Test Method
Shelf Life (25°C)	13	wk	
Thermoset Mix Viscosity (25°C)	350	cP	ASTM D2393

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT