

ADMER™ L2100

Linear Low Density Polyethylene
Mitsui Chemicals Europe GmbH

Message:

ADMER® L2100 is a maleic anhydride grafted LLDPE-based resin, designed for blow molding PE-applications with EVOH or PA. It offers advanced adhesion durability and good processability.

General Information			
Features	Durable		
	Food Contact Acceptable		
	Good Adhesion		
	Good Processability		
Uses	Adhesives		
	Blow Molding Applications		
	Food Service Applications		
	Non-specific Food Applications		
Agency Ratings	FDA Food Contact, Unspecified Rating		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.2	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	52		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	11.0	MPa	
Break	30.0	MPa	
Tensile Elongation (Break)	> 500	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (Area)	No Break		ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	101	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

