

Wanthane® WHT-1685AD

Thermoplastic Polyurethane Elastomer (Polyester)

Wanhua Chemical Group Co., Ltd.

Message:

WHT-1685AD is polyester-based TPU for extrusion molding applications, supplied in form of transparent, translucent, colorless or slightly yellowish film with good workability for high frequency soldering.

Applications:

Package, Exterior Decoration Parts, Fabric Coating.

General Information			
Uses	Packaging		
	Coating application		
	Fabric		
	Decorative parts		
Appearance	Translucent		
	Transparent-Slightly Yellow		
	Colorless		
Forms	Films		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.19	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	85		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress			ASTM D412
100% strain	5.00	MPa	ASTM D412
300% strain	7.00	MPa	ASTM D412
Tensile Strength	15.0	MPa	ASTM D412
Tensile Elongation (Break)	690	%	ASTM D412
Tear Strength	65.0	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	-40.0	°C	ASTM D3417
Optical	Nominal Value	Unit	Test Method
Transmittance	89.0	%	ASTM D1003
Extrusion	Nominal Value	Unit	
Drying Temperature	80.0 - 110	°C	
Drying Time	2.0 - 3.0	hr	
Cylinder Zone 1 Temp.	165	°C	
Cylinder Zone 2 Temp.	170	°C	

Cylinder Zone 3 Temp.	175	°C
Cylinder Zone 4 Temp.	180	°C
Cylinder Zone 5 Temp.	180 - 185	°C

Extrusion instructions

Extruder Feed Section: 160

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

