

REVOLVE® M-56

Polyethylene

Matrix Polymers

Message:

Revolve M-56 is part of a new generation of rotational moulding foam grade which has been designed to give outstanding rigidity and closed cell. Suitable for use in single, double and triple layer applications with any PE grade supplied by Matrix. For processing guidelines please contact one of our representatives in your area.

General Information			
Features	Foamable		
	Good Processability		
	Good Stiffness		
Uses	Foam		
Appearance	Black		
	Colors Available		
	Natural Color		
Forms	Powder		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density ¹	0.230	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR)	3.0	g/10 min	ISO 1133
NOTE			
1.	Foamed		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT