

VINIKA® CE60QC

Flexible Polyvinyl Chloride

Mitsubishi Chemical Performance Polymers, Inc.

Message:

VINIKA® CE60QC is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific for extrusion.
Typical application of VINIKA® CE60QC: Construction Applications

General Information			
Uses	Building Materials		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.40	g/cm ³	JIS K7112
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (10 sec)	60		JIS K6253
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			JIS K6723
Break	8.40	MPa	
100% Strain	3.20	MPa	
Tensile Strain (Break)	370	%	JIS K6723

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT