

Aquathene® CM92949B

Polyolefin
LyondellBasell Industries

Message:

Aquathene CM92949B is a black masterbatch selected by customers for moisture cure applications. CM92949B contains a 40% loading of a fine particle size carbon black for UV weather resistance and an antioxidant to ensure long-term stability and enhance performance. When CM92949B is combined with Aquathene AQ120000 and Aquathene CM04482 or Aquathene CM04483 in the correct ratio this formulation is typically used for USE and USE-2 cable applications.

| General Information | | |
|---------------------|-----------------------------|-------|
| Additive | Antioxidation | |
| | Carbon black (40%) | |
| Features | Good UV resistance | |
| | Crosslinkable | |
| | Good weather resistance | |
| Uses | Wire and cable applications | |
| | Masterbatch | |
| Appearance | Black | |
| Physical | Nominal Value | Unit |
| Density (23°C) | 1.14 | g/cm³ |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT