

MTEGRITY™ LLDPE LL500

Linear Low Density Polyethylene

M. Holland Company

Message:

MTEGRITY™ LLDPE LL500 is a Linear Low Density Polyethylene product. It can be processed by injection molding and is available in North America. Typical application: Additive/Masterbatch. Primary characteristic: good processability.

General Information			
Features	Good Processability		
	Medium Flow		
Uses	Blending		
	Color Concentrates		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.924	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	20	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	13.8	MPa	ASTM D638
Tensile Elongation (Break)	200	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT