

# BP RPPC 1020 TU BLK

Polypropylene Copolymer

Buckeye Polymers, Inc.

## Message:

Product Information: Black Polypropylene Copolymer good for general purpose programs requiring moderate impact resistance.

Features:

Impact Resistance, Good

UV Resistance, Good

Chemical Resistance, Good

Higher Melt Flow available for improved processability

General Information			
Filler / Reinforcement	Talc,10% Filler by Weight		
Additive	UV Stabilizer		
Features	General Purpose		
	Good Chemical Resistance		
	Good Impact Resistance		
	Good Processability		
	Good UV Resistance		
Uses	General Purpose		
Appearance	Black		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	18 to 24	g/10 min	ASTM D1238
Molding Shrinkage - Flow	0.75 to 0.85	%	ASTM D955
Ash Content	15 to 19	%	ASTM D5630
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus (23°C)	> 1100	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	67 to 110	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT