

Nipol® SBR 1502

Emulsion Styrene Butadiene Rubber

Zeon Corporation

Message:

Nipol SBR is produced through emulsion polymerization and is superior to natural rubber in heat aging resistance, abrasion resistance, ozone resistance, chemical resistance, fire retardant performance, and gas penetrability. Furthermore, in terms of tensile strength and bending fracture resistance, performance that is nearly identical to natural rubber can be obtained by optimizing the composition. It is used in a variety of industrial rubber products, such as tires and footwear.

Uses

Tire white wall and carcass, mechanical goods, white or light colored sporting goods, floor covering, shoe soles and heels, refrigerator gaskets.

General Information	
Additive	Antioxidant 2
Features	Antioxidant
Uses	Flooring
	Footwear
	Gaskets
	Sporting Goods
	Tires

Physical	Nominal Value	Unit
Specific Gravity	0.938	g/cm ³
Mooney Viscosity	52	MU
Bound Styrene	23.5	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT