## Epoxies, Ect. 50-3100 (Cat.190)

Epoxy; Epoxide

Epoxies, Etc.

## Message:

50-3100 is designed for the fastest and most continuous high heat transfer. 50-3100 measures several times faster heat dissipation than other commercially available types. The most important breakthrough is the handling of 50-3100. This system can be easily mixed and poured to form a dimensionally stable heat transfer package.

Typical applications include encapsulation of power supplies, transformers, coils, insulators, protective covering for chips, temperature probes, etc...

General Information			
Features	Good Dimensional Stability		
	Good Toughness		
	Semi Rigid		
Uses	Insulation		
	Protective Coverings		
Physical	Nominal Value	Unit	
Molding Shrinkage - Flow	0.30	%	
Thermal	Nominal Value	Unit	
CLTE - Flow	3.0E-5	cm/cm/°C	
Thermal Conductivity	2.2	W/m/K	
Heat Distortion	120	°C	
Operating Temperature	-60.0 to 205	°C	
Uncured Properties	Nominal Value	Unit	
Mix Ratio by Weight (PBW)			
Part A	100		
Part B	5.0		
Density (25°C)	2.00	g/cm³	
Viscosity			
25°C <sup>1</sup>	32	Pa·s	
25°C <sup>2</sup>	180	Pa·s	
Curing Time			
66°C	2.0	hr	
25°C	24	hr	
Pot Life (25°C)	45	min	
Cured Properties	Nominal Value	Unit	
Shore Hardness (Shore D)	90		
Tensile Strength	60.7	MPa	
Compression Strength	103	MPa	
Electric Strength	19	kV/mm	

Relative Permittivity (60 Hz)	6.40	
Volume Resistivity	1.5E+15	ohms·cm
Dissipation Factor (60 Hz)	0.015	
NOTE		
1.	Part B	
2.	Part A	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

