CERTENE™ LLBF-120B

Linear Low Density Polyethylene

Muehlstein

Message:

LLBF-120B is a certified prime resin containing Butene-comonomer, specially designed for production of Blown films for general purpose packaging. LLBF-120B features easy processability with very good film strength as well as wide heat sealing temperature range. LLBF-120B major applications include garment bags, produce bags and liners. Maximum recommended film drawdown is 0.5 mil. LLBF-120B contains no slip and medium antiblock.

General Information					
Additive	Moderate caking resistance				
Features	Low density				
	Workability, good				
	Good heat sealability				
	General				
	Moderate caking resistance				
Uses	Packaging				
	Films				
	Lining				
	Bags				
	General				
Forms	Particle				
Processing Method	Blow film				
Physical	Nominal Value	Unit	Test Method		
Density	0.920	g/cm³	ASTM D1505		
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238		
Films	Nominal Value	Unit	Test Method		
Film Thickness - Tested	25	μm			
secant modulus			ASTM D882		
1% secant, MD: 25 μm	215	МРа	ASTM D882		
1% secant, TD: 25 μm	250	МРа	ASTM D882		
Tensile Strength			ASTM D882		
MD: Yield, 25 µm	12.0	MPa	ASTM D882		
TD: Yield, 25 µm	11.0	МРа	ASTM D882		
MD: Break, 25 µm	45.0	МРа	ASTM D882		
TD: Break, 25 µm	30.0	МРа	ASTM D882		
Tensile Elongation			ASTM D882		
MD: Break, 25 µm	650	%	ASTM D882		
TD: Break, 25 µm	990	%	ASTM D882		

Dart Drop Impact (25 µm)	85	g	ASTM D1709A	
Elmendorf Tear Strength			ASTM D1922	
MD : 25 μm	80	g	ASTM D1922	
TD : 25 µm	550	g	ASTM D1922	
Optical	Nominal Value	Unit	Test Method	
Gloss (45°, 25.4 μm)	65		ASTM D2457	
Haze (25.4 μm)	7.3	%	ASTM D1003	
Additional Information				

This Specimen was compression molded and was tested according to ASTM D1928 Procedure C.

Extrusion	Nominal Value	Unit	
Melt Temperature	200 - 220	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

