

TECHLEN M7462

Polypropylene
DAEHA Co., LTD

Message:

TECHLEN M7462 is a Polypropylene material. It is available in Asia Pacific. Primary attribute of TECHLEN M7462: Impact Resistant.
Typical application of TECHLEN M7462: Automotive

General Information			
Features	High Impact Resistance		
Uses	Automotive Applications		
	Automotive Bumper		
	Automotive Exterior Parts		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.908	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	12	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	13.7	MPa	ASTM D638
Tensile Elongation (Break)	350	%	ASTM D638
Flexural Modulus	588	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact			ASTM D256
-10°C	200	J/m	
23°C	No Break		
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	100	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT